Claims

- 1. (currently amended): A <u>self</u> pressurized, <u>by fluid thermal expansion or phase change</u> (<u>water to steam</u>), <u>fluid filled closed</u> loop solar <u>eellector_collection</u> system for delivering solar energy from a roof mounted <u>collector panel</u> to a <u>domestic</u>-hot water tank including: a pressurization system capable of maintaining system pressures above atmospheric pressure to increase the boiling point of the heat transfer fluid; a <u>pressurized_fluid</u> radiator/overflow/recovery apparatus to catch overflow heat transfer fluid and trapped air and return the fluid to the system <u>by vacuum</u> while keeping air out; a heat transfer fluid to air <u>pressurized_radiator_and_or_solar_collector_pressure_activated_air_vedampersnts_to</u> prevent the solar collectors from overheating during no flow conditions; <u>an-a_water_based_antifreeze_heat_transfer_fluid_to_prevent_damage_from_freezing_in_winter_environments; a flexible umbilical to connect_solar_collector_and_water_tank_heat_exchanger_together; a circulation pump; control system_and_an_double_walled_internal_heat_exchanger_which_is adaptable to <u>existing_the_hot_water_tank</u>, to deliver heat from the heat_transfer_fluid_to_the_hot_water_tank.</u>
- 2. (currently amended): A boiling activated <u>pressurized</u> radiator solar collector overtemperature protection system, which includes a <u>pressurized</u> fluid to air radiator/overflow/recovery apparatus to catch overflow heat transfer fluid and trapped air and return the fluid to the system <u>using vacuum</u> while keeping air out, utilizes no moving actuators, and includes a boiling gas/liquid separator, which allows steam—to reach—a <u>condensed in the pressurized</u> liquid to air radiator and allows—condensed water—to be returned tokept in the pressurized fluid loop, so the sun's heat energy is dissipated to the <u>ambient air flowing over the pressurized radiator and when the collector boiling stops, the sun's heat energy is delivered to the circulating heat transfer fluid and then to the hot water tank.fluid loop.</u>

- 3. (currently amended): A pressure activated solar collector over-temperature protection system which utilizes solar collector air dampers as moving parts, including: a <u>steam</u> pressure activated mechanical actuator, which opens before the systems' regulated pressure is reached; and a set of damper valves, which control airflow over the solar collector panel, so when opened the sun's <u>heat</u> energy is dissipated to the flowing ambient air and <u>then</u> when <u>the dampers are</u> closed the sun's <u>heat</u> energy is delivered to the circulating heat transfer fluid loop-and thus to the hot water tank.
- 4. (<u>cancelled_eurrently_amended</u>): A flexible umbilical assembly that carries and insulates the heat transfer fluid tubing while protecting it from the elements with a clampon "clam-shell" split pipe external covering and includes all electrical connections between the solar collector and the hot water tank.
- 5. (currently amended currently amended): The system according to as in claim 1_5 comprised of a with a 220/115 VAC controller and pump and boiling activated overtemperature protection according to claim 2.
- 6. (<u>currently amended</u>): The system as in claim 1 comprised of a The system according to claim 1, with a 220/115 VAC controller and pump, with pressure activated over-temperature protection, according to claim 3.
- 7. (currently amended currently amended): ThThe system as in claim 1 or claim 2 comprised of a e system according to claim 1, with a photovoltaic panel and low voltage (12VDC) pump, with boiling activated over-temperature protection according to claim 2.
- 8. (currently amended eurrently amended): The system as in claim 1 or claim 3 comprised of a The system according to claim 1, with a photovoltaic panel and low

voltage (12VDC) pump, with pressure activated over-temperature protection-according to elaim 3.

- 9. (new) The system as in claim 2 comprised of a 220/115 VAC controller and pump and boiling activated over-temperature protection.
- 10. (new) The system as in claim 3 comprised of a 220/115 VAC controller and pump, with pressure activated over-temperature protection.
- 11. (new) The system as in claim 2 comprised of a a photovoltaic panel and low voltage (12VDC) pump, with boiling activated over-temperature protection.
- 12. (new) The system as in claim 3 comprised of a photovoltaic panel and low voltage (12VDC) pump, with pressure activated over-temperature protection.